



RITEPOXY-TR™

Translucent Epoxy Grout

Product Description :

RITEPOXY™ TR (Translucent Epoxy Grout - **TWO COMPONENTS**) is designed specially for use in filling up joints of ceramic tiles, vitrified tiles, glass tiles, multi-colour glass mosaic joints where hygiene & light translucent property is of utmost importance. **RITEPOXY™ TR** is easy to mix, chemicals resistant joint filler gives semi-transparent effect

Features :

- Grout with light-translucent property
- Colour fast and 100% stain free
- Chemical resistant with non-toxic properties
- Anti-bacterial and Anti-fungal
- Strong, durable and easy to clean
- Ideal for grouting material for multi-coloured tiles

Area of Application :

- Murals with glass mosaic chips
- Swimming pools area
- Glass Brick walls
- Lounges & Discotheques
- Multi-coloured glass & metal tiles
- Non-vitreous clay tiles
- Marble & Glazed wall tiles
- Glass Mosaic tiles

Application Preparation :

- Clean application area & remove dirt, dust & excess adhesive from tile joints
- Clean the wall or floor before application of tile grout
- Using rubber float fill-up the tile joints

**FOR BETTER APPLICATION
USE A RUBBER FLOAT**

- Wait for 30-45 minutes for joints to harden
- Begin initial clean up with water & gently use scrub pad in circular motion to remove excess materials from the tile/stone surfaces
- Use plenty of clean water until excess grout is cleared from surface
- Remove excess material from the tile surface using wet trowel at 45 degree to the grout joints
- Wait for 2-3 hrs. before giving smooth finish to grout surface with a sponge & hand-glove finger with mild shampoo water
- Wait for 24 hrs. and finally clean the surface with water to remove the epoxy marks
- Surface is now ready to use

Working and Physical Properties :

Sr. No.	Testing Parameter	Test Result
1	Joint width	1-6 mm
2	Pot Life	60 min
3	Time to Foot Traffic	12 hrs
4	Time to Heavy Traffic	24 hrs
5	Specific Gravity	1.60 - 1.70 kg/Ltr.
6	Shrinkage	No Shrinkage
7	Water Cleaning	< 50 min
8	Setting Time	> 3 hrs
9	Sag	No Sagging
10	Compressive Strength	> 5500 Psi
11	Tensile Strength	> 1250 Psi

Mixing Detail :

Particulars	3 kg Pack
Part A - Hardener	180 gm
Part B - Resin Filler Paste	2820 gm

Coverage :

- Varies with width and depth of joint

Storage :

- Store in a cool & dry place. Protect from direct sunlight.

Colour :

- Translucent

Packing Detail :

- Available in 3 kg

Shelf Life :

- 24 months from the date of manufacturing in unopen condition



Inakorji
DISTRIBUTORS
+91 95375 65835