



# MYMIX SEALER 210

## Penetrating Sealer

### Product Description :

**MYMIX SEALER 210** is a liquid with specialized formulation (water based) to seal the porosity of all types of concrete surfaces and natural stones.

**MYMIX SEALER 210** has unique water repellent properties that acts as invisible barrier and provides resistance to moisture and reduce staining, effect of efflorescence, while allowing vapour to escape

### Advantages :

- Acts as a penetrating sealer
- Preserves the natural look
- Ready-mix & easy to use
- U.V. transparent and non-yellowing
- Can be applied on Interior and exterior surfaces
- Highly durable and economical

### Area of Application :

- All kinds of natural stones
- Marbles
- Granites
- Limestone
- Bricks
- Concrete products
- Synthetic marbles
- Fibrous cement material
- Pavers



### Method of Application :

- Clean the surface with a dry cloth and start applying the sealer with the help of a normal paint brush or with cotton cloth with strokes in single direction covering the surface uniformly
- Allow the surface to touch dry before application of the second coat.

The time between two coats should be approx 15-30 mins.

After the second application allow the surface to dry again naturally

- Clean excess sealer from the concrete surface or stone with the help of a dry cotton cloth. If needed buffing has to be done.
- Protect the surface for curing, taking care that no traffic is allowed on the floor area till the prescribed time limit which is 24 to 72 hrs for curing
- Do not apply on damp or wet surfaces
- Avoid application during wet weather condition
- Avoid application on extremely hot surfaces

### Working & Physical Properties :

Sr. No.	Testing Parameter	Test Result
1	Colour	White
2	pH	8 - 10
3	Specific gravity	1 gm/ml
4	Coverage	25 to 100* sq ft per 1 litre per two coat
5	Remarks	Application Brushable

\*Coverage may vary depending on porosity of surface

**Coverage :** Approx. 25 - 100 sq. ft. per litre in two coats

**Colour :** Milky White

**Storage :** Store in a cool & dry place. Protect from direct sunlight.

**Packing Detail :** • Available in 1 Litre & 5 Litre  
• Project pack available on demand

**Shelf Life :** 12 months from the date of manufacturing in unopen condition

